

N-Ch and P-Ch Fast Switching MOSFET

$V_{DS}=20V, I_D=1.0A, R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V, I_D=-1.0A, R_{DS(ON)}=600m\Omega$


➤ General Description

This PAC2332H N&P Channel enhancement mode power field effect transistor is the high density trench technology and this advanced technology can provide excellent $R_{ds(On)}$ performance and efficiency for power switching and load switching application., this device also comply with the RoHS and Green Product requirement with full function reliability approved.

➤ Feature


- Low Offset (Error) Voltage
- Low-Voltage Operation
- High-Speed Circuits
- Low Battery Voltage Operation
- SOT-363 package design

➤ SOT-363



➤ Application

- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories
- Battery Operated Systems
- Load/Power Switching Smart Phones, Pagers
- PA Switch
- Level Switch



➤ Absolute Maximum Ratings

Parameter	Symbol	Rating		Unit
		N-Channel	P-Channel	
Drain-Source Voltage	V_{DSS}	20	-20	V
Gate -Source Voltage	V_{GSS}	± 12	± 12	V
Continuous Drain Current($T_J=150^\circ C$)	I_D	$T_A=25^\circ C$	1.0	A
		$T_A=70^\circ C$	0.7	A
Pulsed Drain Current	I_{DM}	6	-6	A
Continuous Source Current(Diode Conduction)	I_S	1	-1	A
Power Dissipation	P_D	$T_A=25^\circ C$	0.3	W
		$T_A=70^\circ C$	0.2	
Operating Junction Temperature	T_J	-55/150		$^\circ C$
Storage Temperature Range	T_{STG}	-55/150		$^\circ C$

N-Ch and P-Ch Fast Switching MOSFET

$V_{DS}=20V, I_D=1.0A, R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V, I_D=-1.0A, R_{DS(ON)}=600m\Omega$

➤ N-Channel Electrical Characteristics (T_J=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	0.4		1.0	V
Gate Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 12V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=20V, V_{GS}=0V$			1	uA
		$V_{DS}=20V, V_{GS}=0V$ $T_J=85^\circ C$			5	
On-State Drain Current	$I_{D(on)}$	$V_{DS} \geq 5V, V_{GS}=4.5V$	1.2			A
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=4.5V, I_D=1.0A$			280	mΩ
		$V_{GS}=2.5V, I_D=0.8A$			340	
		$V_{GS}=1.8V, I_D=0.7A$			580	
Forward Transconductance	g_{FS}	$V_{DS}=10V, I_D=1.0A$		1		S
Diode Forward Voltage	V_{SD}	$I_S=1.0A, V_{GS}=0V$		0.65	1.2	V
Dynamic						
Input Capacitance	C_{iss}	$V_{DS}=10V, V_{GS}=0V$ $f=1MHz$		70		pF
Output Capacitance	C_{oss}			20		
Reverse Transfer Capacitance	C_{rss}			8		
Total Gate Charge	Q_g	$V_{DS}=10V, V_{GS}=4.5V$ $I_D \equiv 1.2A$		1.06	1.38	nC
Gate-Source Charge	Q_{gs}			0.18		
Gate-Drain Charge	Q_{gd}			0.32		
Turn-On Time	$t_{d(on)}$	$V_{DD}=10V, R_L=20\Omega$ $I_D \equiv 1.2A, V_{GEN}=4.5V$ $R_G=1\Omega$		18	26	ns
	t_r			20	28	
Turn-Off Time	$t_{d(off)}$			70	110	
	t_f			25	40	

N-Ch and P-Ch Fast Switching MOSFET

$V_{DS}=20V, I_D=1.0A, R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V, I_D=-1.0A, R_{DS(ON)}=600m\Omega$

➤ P-Channel Electrical Characteristics (T_J=25° C Unless otherwise noted)







Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.4		-1.0	V
Gate Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 12V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-20V, V_{GS}=0V$			-1	uA
		$V_{DS}=-20V, V_{GS}=0V$ T _J =85°C			-5	
On-State Drain Current	$I_{D(on)}$	$V_{DS} \geq 5V, V_{GS}=4.5V$	0.7			A
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=-4.5V, I_D=-0.6A$			600	mΩ
		$V_{GS}=-2.5V, I_D=-0.5A$			840	
		$V_{GS}=-1.8V, I_D=-0.4A$			1440	
Forward Transconductance	g_{FS}	$V_{DS}=-10V, I_D=-0.4A$		1		S
Diode Forward Voltage	V_{SD}	$I_S=-0.15A, V_{GS}=0V$		0.65	1.2	V
Dynamic						
Input Capacitance	C_{iss}	$V_{DS}=-10V, V_{GS}=0V$ f=1MHz		70	100	pF
Output Capacitance	C_{oss}			20		
Reverse Transfer Capacitance	C_{rss}			10		
Total Gate Charge	Q_g	$V_{DS}=-10V, V_{GS}=-4.5V$ $I_D \equiv -0.25A$		1.0	1.3	nC
Gate-Source Charge	Q_{gs}			0.1		
Gate-Drain Charge	Q_{gd}			0.3		
Turn-On Time	$t_{d(on)}$	$V_{DD}=-10V, R_L=30\Omega$ $I_D \equiv -0.2A, V_{GEN}=-4.5V$ $R_G=10\Omega$		10	15	ns
	t_r			10	15	
Turn-Off Time	$t_{d(off)}$			40	60	
	t_f			30	50	

N-Ch and P-Ch Fast Switching MOSFET

$V_{DS}=20V, I_D=1.0A, R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V, I_D=-1.0A, R_{DS(ON)}=600m\Omega$

➤ Typical Characteristics(N-Channel)








N-Ch and P-Ch Fast Switching MOSFET

$V_{DS}=20V, I_D=1.0A, R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V, I_D=-1.0A, R_{DS(ON)}=600m\Omega$

➤ Typical Characteristics(N-Channel)




N-Ch and P-Ch Fast Switching MOSFET


$V_{DS}=20V, I_D=1.0A, R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V, I_D=-1.0A, R_{DS(ON)}=600m\Omega$


➤ Typical Characteristics(P-Channel)




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance



Gate Charge




On-Resistance vs. Junction Temperature

N-Ch and P-Ch Fast Switching MOSFET


$V_{DS}=20V, I_D=1.0A, R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V, I_D=-1.0A, R_{DS(ON)}=600m\Omega$


➤ Typical Characteristics(P-Channel)




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage Variance vs. Temperature



I_{GSS} vs. Temperature




Normalized Thermal Transient Impedance, Junction-to-Ambient

N-Ch and P-Ch Fast Switching MOSFET

$V_{DS}=20V, I_D=1.0A, R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V, I_D=-1.0A, R_{DS(ON)}=600m\Omega$

➤ Recommand IR Reflow Soldering Thermal Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T_{smin})	150°C
Temperature Max. (T_{smax})	200°C
Time (t_s) from (T_{smin} to T_{smax})	60-120 seconds
Average Ramp-up Rate (t_L to t_P)	3°C/second max.
Liquidous Temperature (T_L)	217°C
Time (t_L) Maintained Above (T_L)	60 – 150 seconds
Peak Temperature	260°C +0°C / -5°C
Time (t_P) within 5°C of actual Peak Temperature	30 seconds
Ramp-down Rate (T_P to T_L)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.

➤ Ordering Information


Part Number	Description	Quantity
PAC2332H	SOT-363 Reel	3000 pcs

N-Ch and P-Ch Fast Switching MOSFET

$V_{DS}=20V$, $I_D=1.0A$, $R_{DS(ON)}=280m\Omega$

$V_{DS}=-20V$, $I_D=-1.0A$, $R_{DS(ON)}=600m\Omega$

➤ Package Information (SOT-363)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

N-Ch and P-Ch Fast Switching MOSFET **$V_{DS}=20V$, $I_D=1.0A$, $R_{DS(ON)}=280m\Omega$** **$V_{DS}=-20V$, $I_D=-1.0A$, $R_{DS(ON)}=600m\Omega$**

DISCLAIMER

- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Paceleader, Paceleader reserve the right to make changes to the information in this document.
- Though Paceleader make effort to improve product quality and reliability, Product can malfunction and fail due to their inherent electrical sensitivity and vulnerability to physical stress, it is the responsibility of the customer, when utilizing Paceleader products, to comply with the standards of safety in making a safe design for entire system and to avoid situation in which a malfunction or failure., In developing a new designs, customer should ensure that the device which shown in this documents are used within specified operatingranges.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Paceleader for any infringements of patents or other rights of the third parties which may result from its use.