



### ➤ General Description

PAE2503W are designed by bi-direction TVS diode, to protect high speed data interfaces. This product has been specifically designed to protect sensitive components which are connected to data and transmission lines from overvoltage caused by ESD (electrostatic discharge), CDE (Cable Discharge Events), and EFT (electrical fast transients). The TVS diode prevents over-voltage on the power line, protecting any downstream components. The low capacitance configuration allows the user to protect high-speed data or transmission lines. This device is optimized for ESD protection of portable electronics. They may be used to meet the ESD immunity requirements of IEC 61000-4-2, Level 4 ( $\pm 15\text{kV}$  air,  $\pm 8\text{kV}$  contact discharge).

### ➤ Feature

- Transient protection for high-speed data lines to IEC 61000-4-2 (ESD)  $\pm 15\text{kV}$  (air),  $\pm 8\text{kV}$  (contact) IEC 61000-4-4 (EFT) 40A (5/50ns)
- Small package saves board space
- Protects up to four I/O lines & power line
- Low capacitance ( $< 3\text{pF}$ ) for high-speed interfaces
- Low leakage current and clamping voltage
- Low operating voltage: 5.0V
- Solid-state silicon-avalanche technology

### ➤ DFN0603-2



### ➤ Application

- USB 2.0 Power and Data Line Protection
- Monitors and Flat Panel Displays
- Digital Visual Interface (DVI)
- 10/100/1000 Ethernet
- Notebook Computer
- SIM Ports
- ATM Interface
- IEEE 1394 Firewire Ports Cellular
- Handsets & Accessories Portable
- Instrumentation
- Digital Cameras
- Video Graphics Cards

### ➤ Maximum Ratings (T<sub>A</sub>=25°C Unless otherwise specified)


Parameter	Symbol	Typical	Unit
Peak Pulse Power ( t <sub>p</sub> = 8/20 μs )	P <sub>pk</sub>	100	W
Maximum Peak Pulse Current ( t <sub>p</sub> = 8/20 μs )	I <sub>PP</sub>	4	A
ESD per IEC 61000 – 4 – 2 (Air)	V <sub>PP</sub>	±15	KV
ESD per IEC 61000 – 4 – 2 (Contact)	V <sub>PP</sub>	±8	KV
Operating Junction Temperature	T <sub>J</sub>	-55 ~ 125	°C
Storage Temperature Range	T <sub>STG</sub>	-55 ~ 150	°C
Lead Soldering Temperature	T <sub>L</sub>	260 ( 10sec )	°C

### ➤ Electrical Characteristics (T<sub>A</sub>=25°C Unless otherwise specified)


Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Reverse Stand – Off Voltage	V <sub>RWM</sub>	Pin 1 to 2 or Pin 2 to 1			5	V
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>t</sub> = 1mA Pin 1 to 2 or Pin 2 to 1	6			V
Reverse Leakage Current	I <sub>R</sub>	V <sub>RWM</sub> = 5V , T=25K Pin 1 to 2 or Pin 2 to 1		0.5	1.0	μA
Clamping Voltage	V <sub>C</sub>	I <sub>PP</sub> = 1A , t <sub>p</sub> = 8/20 μs Pin 1 to 2 or 2 to 1			13	V
Clamping Voltage	V <sub>C</sub>	I <sub>PP</sub> = 4A , t <sub>p</sub> = 8/20 μs Pin 1 to 2 or 2 to 1			15	V
Junction Capacitance	C <sub>J</sub>	V <sub>R</sub> = 0V , f = 1MHz		2	3	pF

### ➤ Typical Characteristics


**Non-Repetitive Peak Pulse Power vs. Pulse Time**




**Power Derating Curve**




**Clamping Voltage vs. Peak Pulse Current**



**Normalized Capacitance vs. Reverse Voltage**



## ➤ Package Information (DFN0603-2)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.275	0.340	0.011	0.013
D	0.270	0.370	0.011	0.015
E	0.570	0.670	0.022	0.026
b	0.200	0.300	0.008	0.012
e	0.330	0.400	0.013	0.016
L1	0.200	0.300	0.008	0.012
L2	0.100	0.190	0.004	0.007
L3	0.100 REF.		0.004 REF.	
L4	0.030 REF.		0.001 REF.	
L5	0.150 REF.		0.006 REF.	

## ➤ Ordering Information

Part Number	Description	Quantity
PAE2503W	DFN0603-2 Reel	10000 pcs

## **DISCLAIMER**

- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Paceleader, Paceleader reserve the right to make changes to the information in this document.
- Though Paceleader make effort to improve product quality and reliability, Product can malfunction and fail due to their inherent electrical sensitivity and vulnerability to physical stress, it is the responsibility of the customer, when utilizing Paceleader products, to comply with the standards of safety in making a safe design for entire system and to avoid situation in which a malfunction or failure., In developing a new designs, customer should ensure that the device which shown in this documents are used within specified operatingranges.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Paceleader for any infringements of patents or other rights of the third parties which may result from its use.