

### ➤ General Description

The PAECxxC Series are ultra low capacitance transient voltage suppressor arrays, designed to protect applications such as portable electronics and SMART phones. This series is available in both unidirectional and bidirectional configurations and is rated at 350 Watts for an 8/20 $\mu$ s waveform.

The PAECxxC Series meets IEC 61000-4-2 (ESD) and IEC 61000-4-4 (EFT) requirements. At higher operating frequencies or faster edge rates, insertion loss and signal integrity are a major concern. This series offers an ultra low capacitance and low leakage current in a miniature SOD-323 package.

### ➤ Feature


- 350 Watts Peak Pulse Power per Line (8 x 20 us Waveform)
- Replacement for MLV (0805)
- Protects One Power or I/O Port
- Low Clamping Voltage
- Available in Multiple Voltages:3.3V,5.0V,8.0V,12V,15V,24V
- Ultra Low Capacitance: 0.8pF (Typical)
- Response Time is < 1 ns
- Meets MSL 1 Requirements
- Solid-state silicon avalanche technology
- ROHS compliant

### ➤ SOD-323



### ➤ Application

- Hand-Held Portable Applications
- Networking and Telecom(Ethernet 10/100/1000 Base T)
- USB Interface
- Automotive Electronics
- Serial and Parallel Ports
- Notebooks, Desktops, Servers



### ➤ Protection solution to meet

- IEC61000-4-2 (ESD)  $\pm$ 15kV (air),  $\pm$ 8kV (contact)
- IEC61000-4-4 (EFT) 40A (5/50ns)

### ➤ Maximum Ratings (TA=25°C Unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (tp=8/20µs waveform)	P <sub>PPP</sub>	350	Watts
ESD Rating per IEC61000-4-2:	Contact	8	KV
	Air	15	
Lead Soldering Temperature	T <sub>L</sub>	260 (10 sec.)	°C
Operating Temperature Range	T <sub>J</sub>	-55 ~ 150	°C
Storage Temperature Range	T <sub>STG</sub>	-55 ~ 150	°C
Lead Solder Temperature – Maximum (10 Second Duration)	T <sub>L</sub>	260	°C

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

\*Other voltages may be available upon request.


1. Non-repetitive current pulse, per Figure 1.

### ➤ Electrical Characteristics (TA=25°C Unless otherwise specified)


Device	V <sub>RWM</sub>	I <sub>R</sub> @ V <sub>RWM</sub>	V <sub>BR</sub> @ 1 mA	V <sub>C</sub>	I <sub>pp</sub> @8/20us	Capacitance		P <sub>PK</sub>
			(Volts)	@ 1 A	(Amps)	@ VR = 0 V, 1 MHz (pF)		
			Min	(V)	Max.	Typ	Max.	
PAEC03C	3.30	5.0	4.00	7.50	20.0	0.8	1.5	350
PAEC05C	5.00	1.0	6.00	9.80	17.0	0.8	1.5	350
PAEC08C	8.00	1.0	8.50	13.6	15.0	0.8	1.5	350
PAEC12C	12.0	1.0	13.3	17.8	11.0	0.8	1.5	350
PAEC15C	15.0	1.0	16.7	23.5	10.0	0.8	1.5	350
PAEC24C	24.0	1.0	26.7	38.0	6.00	0.8	1.5	350

Junction capacitance is measured in VR=0V,F=1MHz


Symbol	Parameter
V <sub>RWM</sub>	Working Peak Reverse Voltage
V <sub>BR</sub>	Breakdown Voltage @ I <sub>T</sub>
V <sub>C</sub>	Clamping Voltage @ I <sub>PP</sub>
I <sub>T</sub>	Test Current
I <sub>RM</sub>	Leakage current at V <sub>RWM</sub>
I <sub>PP</sub>	Peak pulse current
C <sub>O</sub>	Off-state Capacitance
C <sub>J</sub>	Junction Capacitance




### ➤ Typical Characteristics



**Pulse Waveform**



**Non-Repetitive Peak Pulse Power vs. Pulse Time**





**Power Derating Curve**

### ➤ Ordering Information

Part Number	Description	Quantity
PAEC03C~PAEC24C	SOD-323 Reel	3000 pcs


### ➤ Package Information (SOD-323)

Case Material: Molded Plastic. UL Flammability




Dim	Millimeters		Inches	
	Min	Max	Min	Max
A	1.60	1.80	0.063	0.071
B	1.2	1.40	0.047	0.055
C	0.80	0.90	0.031	0.035
D	0.25	0.35	0.010	0.014
E	0.15REF		0.006REF	
H	0	0.10	0	0.004
J	0.08	0.15	0.003	0.006
K	2.50	2.70	0.098	0.106

### Recommended Pad outline



### SOD-323 Reel Dim



Package	Chip Size	Pocket Size B0×A0×K0(mm)	Tape Width	Reel Diameter	Quantity Per Reel	P0	P1
SOD-323	2.60×1.40×1.05	3.30×1.50×1.25	8mm	178mm(7")	3000	4mm	4mm
D0	D1	E	F	K	T	W	
1.5mm	0.5mm	1.75mm	3.5mm	1.0mm	0.2mm	8mm	



### DISCLAIMER

- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Paceleader, Paceleader reserve the right to make changes to the information in this document.
- Though Paceleader make effort to improve product quality and reliability, Product can malfunction and fail due to their inherent electrical sensitivity and vulnerability to physical stress, it is the responsibility of the customer, when utilizing Paceleader products, to comply with the standards of safety in making a safe design for entire system and to avoid situation in which a malfunction or failure., In developing a new designs, customer should ensure that the device which shown in this documents are used within specified operatingranges.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Paceleader for any infringements of patents or other rights of the third parties which may result from its use.