


➤ General Description

This PAN60TJ14J N-Channel enhancement mode power field effect transistor is the high density trench technology and this advanced technology can provide excellent $R_{ds(On)}$ performance and efficiency for power switching and load switching application., this device also comply with the RoHS and Green Product requirement with full function reliability approved.

➤ Feature

- Super Low Gate Charge
- 100% EAS Guaranteed
- Green Device Available
- Excellent CdV/dt effect decline
- Advanced high cell density Trench technology

➤ SOP-8



➤ Application

- Notebook CPU Core-High-Side Switch

➤ Absolute Maximum Ratings

| Parameter | Symbol | Rating | Units |
|---|----------------------|------------|--------------|
| Drain-Source Voltage | V_{DS} | 60 | V |
| Gate-Source Voltage | V_{GS} | ± 20 | V |
| Continuous Drain Current, V_{GS} @ 10V ₁ | $I_D@T_A=25^\circ C$ | 4.5 | A |
| Continuous Drain Current, V_{GS} @ 10V ₁ | $I_D@T_A=70^\circ C$ | 3.5 | A |
| Pulsed Drain Current ₂ | I_{DM} | 18 | A |
| Single Pulse Avalanche Energy ₃ | EAS | 22 | mJ |
| Avalanche Current | I_{AS} | 21 | A |
| Total Power Dissipation ₄ | $P_D@T_A=25^\circ C$ | 1.5 | W |
| Storage Temperature Range | T_{STG} | -55 to 150 | $^\circ C$ |
| Operating Junction Temperature Range | T_J | -55 to 150 | $^\circ C$ |
| Thermal Resistance Junction-ambient ₁ | $R_{\theta JA}$ | 85 | $^\circ C/W$ |
| Thermal Resistance Junction-Case ₁ | $R_{\theta JC}$ | 25 | $^\circ C/W$ |

➤ Electrical Characteristics (T_J=25°C Unless otherwise noted)

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|--|---------------------------------------|--|------|-------|------|-------|
| Drain-Source Breakdown Voltage | BV _{DSS} | V _{GS} =0V, I _D =250uA | 60 | --- | --- | V |
| BVDSS Temperature Coefficient | Δ BV _{DSS} /Δ T _J | Reference to 25°C, I _D =1mA | --- | 0.044 | --- | V/°C |
| Static Drain-Source On-Resistance ₂ | R _{DS(ON)} | V _{GS} =10V, I _D =4A | --- | --- | 40 | mΩ |
| | | V _{GS} =4.5V, I _D =3A | --- | --- | 50 | |
| Gate Threshold Voltage | V _{GS(th)} | V _{GS} =V _{DS} , I _D =250uA | 1.0 | --- | 2.5 | V |
| V _{GS(th)} Temperature Coefficient | Δ V _{GS(th)} | | --- | -4.8 | --- | mV/°C |
| Drain-Source Leakage Current | I _{DSS} | V _{DS} =48V, V _{GS} =0V, T _J =25°C | --- | --- | 1 | uA |
| | | V _{DS} =48V, V _{GS} =0V, T _J =55°C | --- | --- | 5 | |
| Gate-Source Leakage Current | I _{GSS} | V _{GS} =±20V, V _{DS} =0V | --- | --- | ±100 | nA |
| Forward Transconductance | g _{fs} | V _{DS} =5V, I _D =4A | --- | 28.3 | --- | S |
| Gate Resistance | R _g | V _{DS} =0V, V _{GS} =0V, f=1MHz | --- | 2.5 | --- | Ω |
| Total Gate Charge (10V) | Q _g | V _{DS} =48V, V _{GS} =10V, I _D =4A | --- | 19 | --- | nC |
| Gate-Source Charge | Q _{gs} | | --- | 2.6 | --- | |
| Gate-Drain Charge | Q _{gd} | | --- | 4.1 | --- | |
| Turn-On Delay Time | T _{d(on)} | V _{DD} =30V, V _{GS} =10V, R _G =3.3Ω, I _D =4A | --- | 3 | --- | ns |
| Rise Time | T _r | | --- | 34 | --- | |
| Turn-Off Delay Time | T _{d(off)} | | --- | 23 | --- | |
| Fall Time | T _f | | --- | 6 | --- | |
| Input Capacitance | C _{iss} | V _{DS} =15V, V _{GS} =0V, f=1MHz | --- | 1027 | --- | pF |
| Output Capacitance | C _{oss} | | --- | 65 | --- | |
| Reverse Transfer Capacitance | C _{rss} | | --- | 46 | --- | |

➤ Diode Characteristics

| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|--|-----------------|---|------|------|------|------|
| Continuous Source Current _{1,5} | I _S | V _G =V _D =0V, Force Current | --- | --- | 4.5 | A |
| Pulsed Source Current _{2,5} | I _{SM} | | --- | --- | 18 | A |
| Diode Forward Voltage ₂ | V _{SD} | V _{GS} =0V, I _S =1A, T _J =25°C | --- | --- | 1.2 | V |
| Reverse Recovery Time | t _{rr} | I _F =4A, dI/dt=100A/μs, T _J =25°C | --- | 12.1 | --- | nS |
| Reverse Recovery Charge | Q _{rr} | | --- | 6.7 | --- | nC |

Note :

- 1.Pulse width limited by maximum junction temperature.
- 2.The data tested by pulsed, pulse width ≤ 300us, duty cycle ≤ 2%
- 3.The EAS data shows Max. rating. The test condition is V_{DD}=25V, V_{GS}=10V, L=0.1mH, I_{AS}=21A
- 4.Ensure that the channel temperature does not exceed 150°C.
- 5.The data is theoretically the same as I_D and I_{DM}, in real applications, should be limited by total power dissipation.

➤ Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs. Gate-Source




Fig.3 Forward Characteristics Of Reverse




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs. T_J




Fig.6 Normalized $R_{DS(on)}$ vs. T_J




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform




Fig.11 Unclamped Inductive Switching Waveform

➤ Recommend IR Reflow Soldering Thermal Profile




| Profile Feature | Pb-Free Assembly Profile |
|--|--------------------------|
| Temperature Min. (T_{smin}) | 150°C |
| Temperature Max. (T_{smax}) | 200°C |
| Time (t_s) from (T_{smin} to T_{smax}) | 60-120 seconds |
| Average Ramp-up Rate (t_L to t_P) | 3°C/second max. |
| Liquidous Temperature (T_L) | 217°C |
| Time (t_L) Maintained Above (T_L) | 60 – 150 seconds |
| Peak Temperature | 260°C +0°C / -5°C |
| Time (t_P) within 5°C of actual Peak Temperature | 30 seconds |
| Ramp-down Rate (T_P to T_L) | 6°C/second max |
| Time 25°C to Peak Temperature | 8 minutes max. |

➤ Ordering Information

| Part Number | Description | Quantity |
|-------------|-------------|----------|
| PAN60TJ14J | SOP-8 Reel | 2500 pcs |

➤ Package Information (SOP-8)



| SYMBOLS | MILLIMETERS | | INCHES | |
|---------|-------------|-------|--------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.700 | 5.150 | 0.185 | 0.203 |
| B | 3.700 | 4.100 | 0.146 | 0.161 |
| C | 1.23 | 1.753 | 0.048 | 0.069 |
| D | 0.310 | 0.510 | 0.012 | 0.020 |
| F | 1.070 | 1.470 | 0.042 | 0.058 |
| H | 0.160 | 0.254 | 0.006 | 0.010 |
| I | 0.050 | 0.254 | 0.002 | 0.010 |
| J | 5.750 | 6.250 | 0.226 | 0.246 |
| M | 0.400 | 1.270 | 0.016 | 0.050 |

DISCLAIMER

- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Paceleader, Paceleader reserve the right to make changes to the information in this document.
- Though Paceleader make effort to improve product quality and reliability, Product can malfunction and fail due to their inherent electrical sensitivity and vulnerability to physical stress, it is the responsibility of the customer, when utilizing Paceleader products, to comply with the standards of safety in making a safe design for entire system and to avoid situation in which a malfunction or failure., In developing a new designs, customer should ensure that the device which shown in this documents are used within specified operatingranges.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Paceleader for any infringements of patents or other rights of the third parties which may result from its use.